

bodytone

LINEABOLD



PULL DOWN INDOOR

MODEL **SR02-E**



DIMENSIONS

148 x 160 x 193 cm

NET WEIGHT

130 kg

WORK AREA

Upper train.

BASE BASE

4 anti-skid caps.

HANDLES

Anodised ALUMINIUM, knurled for better grip.

BEARINGS

SKF double tapered roller bearings, housed in a closed, anti-backlash bushing, ensuring constant direction of movement.

ADJUSTMENT LEVERS

Pop-pin adjustable seat.

Adjustment system by means of a single bolt, made of techno-polymer with a breakage rate of 750 kg.

AXLES

Laser cut 10mm thick plates with another 10mm thick plate for reinforcement, to achieve a smooth movement without looseness or twisting caused by continuous use or load.

LOAD CAPACITY

310mm supports for 6 Bodytone discs of 20kg per arm (up to 240kg for training).

STRUCTURE

110 x 52 mm steel tubes with 3 mm thickness.

Welded in accordance with UNE 10219 regulations, quality S-275-J0H. Enriched and optimised to maintain a constant section in the bending process, thus avoiding sensitive areas and minimising the breakage rate. Cold bending process, by means of a 4-roller system, avoiding any deformation in the process and maintaining the physical characteristics throughout the piece.

Closed welding perimeter in the structural points and joint plates.

PAINTING PROCESS

3 coats of paint.

Steel pickled and stabilised by total immersion of the parts in different degreasing solutions to guarantee a perfect and complete cleaning of the base material.

perfect and complete cleaning of the base material.

Anti-rust primer to guarantee adequate insulation from internal oxidation and good paint adhesion.

2 final coats of polyester epoxy powder paint, dried at 240oC.



PULL DOWN INDOOR Highlights



SEAT ADJUSTABLE IN SEVERAL
HEIGHTS



STURDY AND STRONG STEEL
STRUCTURE



LOAD CAPACITY