

bodytone

BOLDLINE



PULL DOWN OUTDOOR

MODEL **SR02-O**

**DIMENSIONS**

148 x 160 x 193 cm

NET WEIGHT

130 kg

WORK AREA

Upper train.

BASE BASE

4 anti-skid caps.

HANDLES

Anodised ALUMINIUM, knurled for better grip.

BEARINGS

SKF double tapered roller bearings, housed in a closed, anti-backlash bushing, ensuring constant direction of movement.

ADJUSTMENT LEVERS

Pop-pin adjustable seat.

Adjustment system by means of a single bolt, made of techno-polymer with a breakage rate of 750 kg.

AXLES

Laser cut 10mm thick plates with another 10mm thick plate for reinforcement, to achieve a smooth movement without looseness or twisting caused by continuous use or load.

LOAD CAPACITY

4 on each arm, 5 or 10 Kg. discs (discs not included).

STRUCTURE

110 x 52 mm steel tubes with 3 mm thickness. Welded in accordance with UNE 10219 regulations, quality S-275-J0H. Enriched and optimised to maintain a constant section in the bending process, thus avoiding sensitive areas and minimising the breakage rate. Cold bending process, by means of a 4-roller system, avoiding any deformation in the process and maintaining the physical characteristics throughout the piece. Closed welding perimeter in the structural points and joint plates.

PAINTING PROCESS

5 coats of paint. 200 microns Steel pickled and stabilised by total immersion of the parts in different degreasing solutions to guarantee a perfect and complete cleaning of the base material. Zinc phosphate anti-rust primer to guarantee adequate insulation from internal oxidation and good paint adhesion. 3 final coats of polyester epoxy powder paint, special for exteriors, drying at 240oC. Top coat of polyester protective varnish.



PULL DOWNOUTDOOR

PULL DOWNOUTDOOR Highlights



SEAT ADJUSTABLE IN SEVERAL
HEIGHTS



STURDY AND STRONG STEEL
STRUCTURE



LOAD CAPACITY