

# bodytone

## BOLDLINE



## SHOULDER PRESS

### INDOOR

MODEL **SR03-E**

**DIMENSIONS**

184 x 121 x 143 cm

**NET WEIGHT**

160 kg

**WORK AREA**

Upper train.

**BASE BASE**

4 anti-skid caps.

**HANDLES**

Anodised ALUMINIUM, knurled for better grip.

**MATERIALS AND FINISHES**

20 mm thick rubber finish on the disc holders. 50 mm thick rubber finishes to support the moving parts.

**BEARINGS**

SKF double tapered roller bearings, housed in a closed, anti-backlash bushing, ensuring a constant direction of movement.

**ADJUSTMENT LEVERS**

Pop-pin adjustable seat.

Adjustment system by means of a single pin, made of techno-polymer with a breakage rate of 750 kg.

**LOAD CAPACITY**

Laser-cut 10mm thick plates with another 10mm thick plate for reinforcement, to achieve a smooth movement without looseness or torsion caused by continuous use or load.

## STRUCTURE

Steel tubes of 110 x 52 mm with 3 mm thickness. Welded in accordance with UNE 10219 regulations, quality S-275-J0H. Enriched and optimised to maintain a constant section in the bending process, thus avoiding sensitive areas and minimising the breakage rate. Cold bending process, by means of a 4-roller system, avoiding any deformation in the process and maintaining the physical characteristics throughout the piece. Closed welding perimeter in the structural points and joint plates.

## PAINTING

3 coats of paint.

Steel pickled and stabilised by total immersion of the parts in different degreasing solutions to guarantee a perfect and complete cleaning of the base material.

perfect and complete cleaning of the base material.

Anti-rust primer to guarantee adequate insulation from internal oxidation and good paint adhesion.

2 final coats of polyester epoxy powder paint, dried at 240oC.



# SHOULDER PRESS<sup>INDOOR</sup>

## Highlights



SEAT ADJUSTABLE IN SEVERAL  
HEIGHTS



STURDY AND STRONG STEEL  
STRUCTURE



LOAD CAPACITY