

# bodytone

## BOLDLINE



## CHEST INCLINED OUTDOOR

MODEL **SR04-O**

**DIMENSIONS**

191 x 107 x 175 cm

**NET WEIGHT**

197 kg

**WORK AREA**

Upper frame.

**HANDLES**

Anodised ALUMINIUM, knurled for better grip.

**LOAD CAPACITY**

4 on each arm, 5 or 10 kg discs (discs not included).

**MATERIALS AND FINISHES**

20 mm thick rubber finish on the disc holders. 50 mm thick rubber finishes to support the moving parts.

**BEARINGS**

SKF 6205 2Z. STAINLESS STEEL. Double tapered roller bearings, housed in a closed, anti-backlash bushing, ensuring a constant direction of movement.

**ADJUSTMENT LEVERS**

AISI 316 stainless steel seat post, special anti-corrosion in marine environments. Adjustable with 8 laser engraved positions. Adjustment system by means of a single bolt, made of techno-polymer with a breakage rate of 750 kg.

## STRUCTURE

Steel tubes 110 x 52 mm with 3 mm thickness. Welded in accordance with UNE 10219 regulations, quality S-275-J0H. Enriched and optimised to maintain a constant section in the bending process, thus avoiding sensitive areas and minimising the breakage rate. Cold bending process, by means of a 4-roller system, avoiding any deformation in the process and maintaining the physical characteristics throughout the piece. Closed welding perimeter in the structural points and joint plates.

## PAINTING PROCESS

5 coats of paint. 200 microns Steel pickled and stabilised by total immersion of the parts in different degreasing solutions to guarantee a perfect and complete cleaning of the base material. Zinc phosphate anti-rust primer to guarantee adequate insulation from internal oxidation and good paint adhesion. 3 final coats of polyester epoxy powder paint, special for exteriors, drying at 240°C. Surface coat of protective polyester varnish.



# CHEST INCLINED OUTDOOR Highlights



SEAT ADJUSTABLE TO  
VARIOUS HEIGHTS



STURDY AND STRONG STEEL  
STRUCTURE



LOAD CAPACITY