

bodytone

BOLDLINE



INCLINE PRESS

INDOOR

MODEL **SR06-E**

**DIMENSIONS**

250 x 188 x 154cm

NET WEIGHT

268kg

SECURITY SYSTEM

Safety Lever.

GRIPS

Anodized ALUMINUM, knurled to improve grip.

BEARINGS

SKF double tapered roller bearing, housed in a closed, anti-backlash bushing, ensuring a constant direction of movement.

ADJUSTMENT LEVERS

Backrest adjustable by pop-pin. Adjustment system by means of a single bolt, made of techno-polymer with a breaking index of 750 kg.

LOADING CAPACITY

310 mm supports for 6 Bodytone discs of 20 kg per arm (up to 240 kg for training).

AXES

10mm thick plates laser cut with another 10mm thick plate to reinforce, to achieve a smooth movement without gaps or twists produced by continuous use or load.

STRUCTURE

Steel tubes of 110 x 52 mm with 3 mm thickness. Welded in accordance with the UNE 10219 regulation, quality S-275-J0H. Enriched and optimized to maintain a constant section in the bending process, thus avoiding sensitive areas and minimizing the rate of breakage. Cold bending process, by means of a 4-roller system, avoiding any deformation in the process and maintaining the physical characteristics of the entire piece. Closed perimeter welding at structural points and connection plates.

PAINTING PROCESS

3 coats of paint. Pickled and stabilized steel by total immersion of the parts in different degreasing solutions to guarantee a perfect and complete cleaning of the base material. Anti-rust primer to ensure proper isolation of internal oxidation and good paint adhesion. 2 final coats of epoxy polyester powder paint, drying at 240°C.



INCLINE PRESS^{INDOOR}

Highlights



ADJUSTABLE SEAT IN VARIOUS HEIGHTS



ROBUST AND FIRM STEEL STRUCTURE



LOADING CAPACITY