

bodytone

BOLDLINE



BACK ROW

INDOOR

MODEL **SR07-E**



DIMENSIONS

147 x 171 x 133 cm

NET WEIGHT

132 kg

WORK AREA

Upper train.

BASE BASE

4 anti-skid pads.

BEARINGS

SKF double tapered roller bearings, housed in a closed, anti-backlash bushing, ensuring a constant direction of movement.

ADJUSTMENT LEVERS

Pop-pin adjustable backrest.
Adjustment system by means of a single pin, made of techno-polymer with a breakage rate of 750 kg.

HANDLEBARS

Anodised ALUMINIUM, knurled for better grip.

AXLES

Laser-cut 10mm thick plates with another 10mm thick plate for reinforcement, for smooth movement without looseness or twisting caused by continuous use or load.

LOAD CAPACITY

310 mm supports for 6 Bodytone discs of 20 kg per arm (up to 240 kg for training).

MATERIALS AND FINISHES

20 mm thick rubber finishes on disc holders. 50 mm thick rubber finishes to support moving parts.

STRUCTURE

110 x 52 mm steel tubes with 3 mm thickness. Welded in accordance with UNE 10219 regulations, quality S-275-J0H. Enriched and optimised to maintain a constant section in the bending process, thus avoiding sensitive areas and minimising the breakage rate. Cold bending process, by means

of a 4-roller system, avoiding any deformation in the process and maintaining the physical characteristics throughout the piece.
Closed welding perimeter in the structural points and joint plates.

PAINTING PROCESS

3 coats of paint.

Steel pickled and stabilised by total immersion of the parts in different degreasing solutions to guarantee a perfect and complete cleaning of the base material.

perfect and complete cleaning of the base material.

Anti-rust primer to guarantee adequate insulation from internal oxidation and good paint adhesion.

2 final coats of polyester epoxy powder paint, dried at 240oC.



BACK ROW^{INDOOR} Highlights



SEAT ADJUSTABLE TO
VARIOUS HEIGHTS



STURDY AND STRONG STEEL
STRUCTURE



LOAD CAPACITY