bodytone

FORZA **HERO**



FH55

PRONE LEG CURL

FORZAHERO

This new line is a selection of Bodytone's premium strenght machines, focusing in the user for an excelent training results. Discover all >>>



Connectivity pack screen 9" and NFC (optional)



High quality termoplastic covers



Carbon fiber finish



Ultrasilent bearings



Digital counter



Bottle and mobile holder



Upholstery ABS covers



Non-slip PVC grips with aluminium caps

SCREENTECHNOLOGY

MONITORIZE
YOUR TRAINING

IMPROVE THE PRECISION
OF YOUR WORKOUTS

AT THE TIME



CONNECTED TO YOUR CENTER'S APP

powered by






CONNECTIVITY PACK SCREEN 9" AND NFC (OPTIONAL)











FH55

EXERCICE

Lying hamstring curl machine, isolating semitendinosus and semimembranosus biceps femoris.

DIMENSIONS

WEIGHT

WEIGHT PLATES

118 x 144 x 162 cm

139 kg

107 kg (7 kg/plate)



STRUCTURE

Plate structure part: $140 \times 75 \text{ mm}$ carbon steel tube. Functional part: oval carbon steel tube of $100 \times 50 \text{ mm}$ and round tube of 60 mm diameter. Welded by robotic process, projection free.

BEARINGS

Ultra-quiet ball bearings with smooth sliding, allowing smooth travel of the exercice more fluent and pleasant.

Measures 52 x 15 mm.

PULLEYS

V-groove nylon. With an internal bearing and quiet operation. Step diameter: 95 mm

PLATE GUIDES

Stainless steel plate guides. Hardened double chrome treatment for better sliding.

STEEL WIRES

PVC coated and 5 mm in diameter, with smooth and safe performance. Breakage index test: 1,000 kg. Safety terminal with steel ball joints.

WEIGHT PLATES

107 kg as standard, with 7 kg plates. Ultra-quiet movement. protective stops rubber on anti-knock base. protective stops of PVC between anti-knock plates.

WEIGHT SELECTOR

Magnetic, color-coded plates by intensity level, and safety lanyard.



REPEATCOUNT

As standard, integrated into the fairing.

GRIPS

Non-absorbent non-slip PVC.

BACKS AND UPHOLSTERY

Back, headrest and seat made of foam, upholstered in imitation leather, anti-allergic and easy to clean, with a carbon fiber effect texture.

MATERIALS AND FINISHES

High quality in its finishes.

3.5 mm thermoplastic ABS ferrules.

BASES

Covered in non-slip rubber.

MAINTENANCE AND LUBRICATION

Lubrication of bearings and calibrated steel guides.

PAINTING PROCESS

3 coats of paint. Pickled and stabilized steel by total immersion of the parts in different degreasing solutions to guarantee a perfect and complete cleaning of the base material. Anti-rust primer to ensure proper isolation of internal oxidation and good paint adhesion. In addition, it has 2 final layers of epoxy polyester powder paint dried at 240°C.

DESIGN PROCESS

Study of biomechanics and ergonomics under the supervision of associated professionals and athletes. After a long design period; From the sketch, engineering research, prototyping and testing by professional athletes, our products go to market.

bodytone